

CONTENTS

DATA TRANSMISSION AND PROCESSING

S.N. Kirillov, D.E. Krysyayev. ALGORITHMS OF THE ESTIMATION PARAMETER CONVOLUTIONAL CODE AT ACTION OF AWGN

It is designed algorithms estimations parameter binary convolutional codes on base of the decision of the system of the linear algebraic equations in GF2. It organized simulation modeling algorithm at action of the broadband hindrance. It shown that optimum algorithm allows to produce the estimation a pair-metre convolutional codes with reliability more than 97,5% under SNR not less -1 db.3

A.A. Batenkov, K.A. Batenkov. MANY-DIMENSIONAL SIGNAL ENSEMBLES SYNTHESIS FOR GAUSSIAN DISCRETE CHANNEL

Generation target setting of signal ensemble is considered that is optimal in compliance with commonly used criterion at communications development – minimum average Bayes risk criterion. The claim about many-dimensional signal ensembles synthesis opportunity for discrete channel with additive white Gaussian noise on the basis of optimization problem with differentiable criterion function and constraint is proved.....7

A.I. Novikov, M.E. Ilyin. THE ALGORITHM OF RESTORATION SUBORDINATED AND MISING DATA

In article examine problems restore missing statistical data subordinated additional equations. Authors suggest two methods for correction. In first method seek the similar “neighbor” and it data insert instead of missing. In second method authors use regression. Estimates and errors are calculated.....14

A.A. Ribolovlev, O.O. Basov. IDENTIFICATION ALGORITHM FOR GILBERT’S COMMUNICATION CHANNEL

Possibilities of Gilbert’s communication channel parameter estimation in speech pause are considered. The expressions linking channel error parameters with their estimation in a periodic speech pause are obtained. For the check simulation modeling is organized. Modeling positive result has allowed offering the identifications algorithm for Gilbert’s communication channel in the speech pause.....18

RADIOTECHNICAL AND MEASURING SYSTEMS

V.I. Koshelev, I.S. Kholopov. INCREASE OF PROBABILITY OF DETECTION OF THE TARGETS IN RADAR SYSTEMS WITH RECOGNITION OF CLUTTER TYPES

The criterion of efficiency of recognition of deliberate masking clutters on the basis of Bayes’s rule in which as penalties for wrong decisions losses in probability of correct detection of the target are accepted is entered. The heuristic algorithm of classification of the clutters, based on an estimation of width of a spectrum and a spectral dynamic range of clutters is offered. The comparative analysis of efficiency optimum and heuristic algorithms of recognition is done.23

V.K. Klochko, A.A. Kookolev. METHODS OF FORMING IMAGES IN A BOARD RADIO- AND THERMAL-LOCATORS

Methods of operation at complex amplitudes of reflected signals for the forming of radio-images of a surface and objects in multi-channels board RLS and RTLS are suggested and investigated.

Methods permit to increase resolving ability of RLS by angle coordinates and velocity of getting amplitude images by increasing the number of measure channels and making operations in matrix form.....27

A.L. Vinogradov, Y.L. Vinogradov, S.Y. Fedorov. EQUIVALENT ENVELOPE TRANSFER FUNCTION FOR AMPLITUDE MODULATION SYSTEMS

Method of modulation envelope transfer function finding for amplitude modulation systems is proposed. Examples of envelope transfer function for standard dynamic element is considered. Comparative analysis what had shown adequacy of initial and equivalent systems dynamic performance is done.....31

V.M. Berdnikov. THE ANALYSIS OF THE NOISE STABILITY EXISTING AND PERSPECTIVE SIGNALS SATELLITE NAVIGATING SYSTEMS

Analysed a noise stability of existing and perspective signals of satellite navigating systems a method of imitating modelling on the computer. It is shown, that use of perspective signals in the conditions of influence of a various sort of hindrances allows to receive a prize in accuracy of definition of co-ordinates of the.....36

V.G. Andrejev, S.A. Yukin. CORRECTION OF THE RADAR IMAGE FORMED IN MODE OF DOPPLER NARROWING BEAM

The correction method of the radar image distortions formed by onboard radar systems with Doppler narrowing beam, in front hemisphere is offered at low-level flight is considered. Indemnification of influence parasitic components within the limits of line of equal Doppler speeds is carried out on basis of the information received from the auxiliary reception channel. The prize in comparison with a classical method Doppler narrowing makes 13,67 dB for an analyzed radio-locating situation.....39

COMPUTER SCIENCE AND APPLIED MATHEMATICS

E.V. Larkin, A.V. Pushkin. THE MODEL OF USING THE TARGET EQUIPMENT IN TRAINING SIMULATORS

The research of moving the cabin of moving terrain object like a mass, provided with springs is executed. The influence of the gun's shot to the movement of moving terrain object is shown. The mathematical model, permissive to imitate movement of the moving terrain object in training simulators is obtained.....45

D.E. Korytchinkov, A.A. Trubitsyn, A.A. Dyagilev, M.V. Zubkov. NUMERICAL MODELING MAGNETIC FIELD OF SOLENOID

Algorithm and software of a solenoid magnetic field modeling are developed. Testing of offered strategy on problems with analytical solutions is carried out.....49

R.N. Akinshin, F.F. Biryukov, I.N. Efremov, A.A. Burevlev. MODELS OF DANGEROUS INFLUENCES ON PROTECTED INFORMATION SYSTEM

The mathematical of an estimation probability parameters of safety of the information in conditions of possible realization of dangerous influences on protected system is offered.....52

T.L. Lvova. THE EXISTING QUASIPERIODIC MODE OF MATHEMATIC MODEL OF LINEAR ELECTRIC CIRCUIT

The method for determination conditions of existing nonzero quasiperiodic mode in the linear electric circuit is offered. The received results is used for determination quasiperiodic mode of linear electric circuit.....55

M.A. Korzhavchikov. NUMERICAL SIMULATION OF THE DIELECTRIC PROPERTIES OF THE WET DISPERSE SYSTEMS

The calculation of effective permittivity is described for the spatial-periodic models of the disperse system. The procedure is tested on the model of cubic inclusions and model of interpenetrate components. A method of evaluation of the water distribution on the solid bodies with any shape is proposed. The sedimentation of water on condensation centres fixed at nodes of the cubic lattice is researched. The effective permittivity as a function of the water content is calculated for the wet packings of spheres; the influence of the capillary hysteresis on the dielectric loss angle tangent is investigated.....59

ELECTRONICS

A.P. Avachev, S.P. Vikhrov, N.V. Vishnyakov, I.G. Utochkin, K.V. Mitrophanov. INVESTIGATION OF STRUCTURAL AND ELECTROPHYSICAL CHARACTERISTICS OF A-Si:H FILMS BY AFM

The calculation procedure of concentration of the surface and volumetric states and the localized electrically active state density in amorphous hydrogenated silicon films by results of measuring the surface potential by an atomic-force microscopy (AFM) is offered. The correlation of microstructural parameters (medial diameter and height of clusters), defined by AFM, with the physical parameters calculated by the offered procedure is shown.....66

E.V. Ovchinnikova, V.A. Fatkin. FEATURES OF BUILDING MODELS OF THE PROCESS FOR OBTAINING DIELECTRIC COATINGS

An option of building an extended mathematical model of the process for obtaining dielectric coatings used in manufacturing of radioelectronics' components is presented. The proposed approach allows modeling and forecasting the state of every functional module of the process as well as its final results71

V.V. Gudzev, V.G. Litvinov, M.V. Zubkov, A.J. Klochkov. DEEP LEVELS IN PtSi/Si SCHOTTKY DIODES

Results of deep levels defects spectra investigations by the deep level transient spectroscopy in the PtSi/Si schottky diodes with different technologies of the insulator etching during the n-p-n transistor base formation are presented. The analysis of the deep levels nature is discussed.....76

J.V. Tcherkasova, A.S. Ivanikov. RESEARCH OF THE MECHANISM OF DEVELOPMENT OF DISRUPTION IN VACUUM CONTACTS

Results of research of the mechanism of development of disruption in vacuum contacts, operated by a magnet, are considered. The computer model of formation of electric disruption is developed. Results of modelling (dependence of intensity of an electric field and a current of autoelectronic issue on time) are resulted80

V.V. Soldatov. THE REGIME FACTORS INFLUENCING DURABILITY GAS-DISCHARGE DISPLAY PANELS

Scientific researches parameters gas-discharge indicators of a direct current are investigated. The purpose of research the development of the device for measurement of a pressure {voltage} of occurrence of the category, time of delay of occurrence of the category and a pressure, voltage maintenance gas-discharge indicators of individual using. The device is created, allowing to automate by means of the personal computer process of measurement of parameters that raises {increases} speed of measurement of parameters and their reliability84

V.I. Yasevich, S.M. Karabanov, O.G. Lokshtanova, L.V. Shishkina. INVESTIGATION OF COPPER-NICKEL ELECTRODEPOSITION ON THE REED SWITCH CONTACTS

Processes of the electrodeposition of one of the most perspective contact coatings for reed switches - copper-nickel alloy have been investigated. The main dependences have been obtained

that allow to develop technological process of contact coating formation on the basis of copper-nickel alloy, allowing to replace expensive coatings based on gold and ruthenium, when high technical characteristics of reed switches are retained.....89

BRIEF REPORTS

E.V. Sholudiko. PROSPECTS OF THE DEVELOPMENT NATURAL MONOPOLY IN RUSSIAN FEDERATION AND METHODS OF THE REGULATION BY STATE TO THEIR ACTIVITY

Broughted information on prospect of the development natural monopoly to Russian Federation, their reformation on base of the systems of the government regulation, improvements of the methods of the pricing, structurisation of the branches to industry, thought-out investment politicians state. It Is given analysis to histories of the formation and prospects of the development three the most largest monopolies to Russian Federation (the PARADISE «EES Russia», OAO «Gazprom», OAO «RZHD»). The Confirmed conclusion about that that government regulation natural monopoly is one of the main factor, providing normal operating the economy of the country.....93

E.N. Prokaznikova. THE FEATURES OF CONSTRUCTION TEXTILE PRODUCTION DETAIL A PATTERN FOR CAD OF TEXTILE INDUSTRY

An procedure of construction textile production detail a pattern is suggested. The methods of construction a pattern compared. Support points for construction a pattern with help Bezier curves are classified. The rules of support points tensors creation is defined97

THE ITEMS OF INFORMATION ON THE AUTHORS101