CONTENTS

DATA TRANSMISSION AND PROCESSING

V.K. Zlobin, A.M. Kochergin. ALGORITHMS AND TECHNOLOGIES OF IMAGE PREPROCESSING IN THE EARTH REMOTE SENSING DATA CATALOGING SYSTEMS Algorithms and technologies of image preprocessing in the Earth remote sensing data cataloging systems are shown. They allow in pace of data reception from modern remote sensing systems to provide the space videodata address distribution in archives, its evaluation and, if necessary, the improvement of its quality
V.V. Eremeev, E.P. Kozlov. AUTOMATIC MATCHING OF IMAGES FROM GEOSTATIONARY SPACE-BASED EARTH OBSERVING SYSTEMS USING ELECTRONIC MAPS
A geodetic connection technology of images received from geostationary satellites is examined. The technology is based on automatic combining of unique patches of coastlines, placed on space images, with binary masks, which are formed from electronic maps and allow for coastlines topology as well as brightness, land and water surface positioning
Yu.M. Korshunov. MODELING MULTIDIMENSIONAL STATISTICAL DATASET ALONG WITH GIVEN CORRELATION PROPERTIES The algorithm letting to obtain the multidimensional statistical dataset using the given covariance matrix is described. The correlation properties of the obtained dataset are tight to the properties conditioned by the given covariance matrix
A.A. Fefelov. ESTIMATION OF QUASI-SINGULAR INTEGRALS AT NUMERICAL EMBODYING THE METHOD OF BOUNDARY ELEMENTS IN THREE-DIMENSIONAL NOT AXIALLY SYMMETRIC PROBLEMS OF THE THERMAL CONDUCTION The procedure of a numerical estimation of the integrals entering in the second formula of Green at a task solution about searching of value of temperature in points near to defining boundaries of three-dimensional not axially symmetric area is featured
V.V. Strotov. IMAGE SHIFTING PARAMETERS ESTIMATION IN MOVEMENT DETECTION TASKS Survey of base image shifting estimation approaches in different movement detection tasks is submitted. Algorithm of shift parameters estimation, based on reference areas selecting and their tracking is proposed. Results of this algorithm statistical examination are given
B.A. Alpatov, P.V. Babayan. EXTRACTION OF MOVING TARGETS FROM THE MULTISPECTRAL IMAGE SEQUENCE, DISTORTED WITH GEOMETRIC TRANSFORMATIONS In this paper new algorithm of moving targets extraction from multispectral image sequence is offered. The mathematical model, used during algorithm development, takes into consideration the presence of geometrical distortions, caused by image sensor motion and atmospheric nonuniformity
V.A. Zenin, A.E. Kuznetsov, V.I. Pobaruev. ALGORITHM OF RADIOMETRIC CORRECTION OF IMAGES WITH THE NON-UNIFORM PLOT, RECEIVED FROM THE SPACE VEHICLE «RESOURCE DK» The algorithm of radiometric correction of the images, based on preliminary clusterization of picture and the subsequent processing of everyone cluster on the own parameters is offered. Ways of acceleration of its work due to thin out images and multithreaded calculations that has led to reduction in an operating time on 72 % are described. Results of processing of the real data, proving advantages of the offered approach in comparison with traditional are shown

RADIOTECHNICAL AND MEASURING SYSTEMS

V.K. Klochko. RADIOIMAGE THE RESOLUTION ABILITY Three-dimensional radio-image of surface and objects on surface forming algorithm with higher resolution ability by angle coordinates is offered	9
S.N. Kirillov, V.T. Dmitriev, D.E. Krysyaev S.S. Popov. STUDY QUALITY SENT SPECTINFORMATION UNDER DIFFERENT COMBINATION OF THE CODING THE SOURCE AND CHANNEL RELATIONSHIP IN CONDITION OF THE ACTION OF THE HINDRANCES IN CHANNEL RELATIONSHIP The Organized study to stability algorithm joint coding the source and channel relationship at transmission of speech information to action broadband, narrow-band and structured hindrances. The analyzed codeks of the source on base pulsed-code inflexion (IKM), adaptive delta-inflexions (ADM) and adaptive differential IKM (ADIKM) and canal antinoise codeks on base of the codes Hemming and Bouza-CHoudhuri-Hokvingema. They are shown optimum combinations source and channel codeks relationship for miscellaneous send rate and type of the hindrances in channel5	D N
A.S. Bogdanov, V.P. Lichshishin. FREQUENCY CHARACTERISTICS OF A RESONANCE AMPLIFIED OF POWER WITH DIVIDED LOAD	R
Frequency characteristics of resonance amplifiers of power with divided load are considered. It is shown that worker passband such stages can be limited not only by a value of a factor of power transfer, but also a value of a factor to stability, which on edges worker band of frequencies must remain in permissible limits. An approach to building of schemes of stages of resonance amplifiers of power with divided load, allowing get the more even frequency dependencies of factors to stability in permissible range of the change of their values is offered	6
A.A. Minko. IDENTIFICATION OF LINEAR OBJECT BY REACTION ON HARMONIC SIGNAL The algorithm of the generalized identification is offered on the basis of integral two-parametric transformations of Gausse of linear stationary object by its reaction on a sinusoidal signal. Experimental verification of capacity of the developed algorithm, confirming its very high efficiency, is conducted.	3
O.K. Abramov, V.M. Bezuglov. THE NOISE-RESISTANT MEASUREMENT OF A LITTLE SEISMIC SIGNALS	\mathbb{C}
It is considered the problems of the measurement of a little seismic signals with combinations of high industrial noise and earth tremors. A solution of this task is very importans for investigations of a seismic regime in the greate industrial areals	8
T.A. Akimenko, E.V. Larkin, O.A. Luchanskiy. TECHNICAL VISION SYSTEM OF MOBILE ROBO VEHICLE	Γ
A method of blur parameters evaluation of images being formed by mobile robot vehicle technical vision system is proposed. Dependencies for vision system space-frequency transfer function, those take into account vision system truck oscillations on vertical linear and longitudinal/diametrical angle coordinates, are obtained	7
Y.A. Aldunin. CLIENT-ORIENTED MODELS AND WAYS OF ITS REALIZATIONThis article is about main client-oriented consistency models. Ways of its realization are given then. Main problems of realization are described at he end of article with its ways of the decision8	0

COMPUTER SCIENCE AND COMPUTER ENGINEERING

T.G. Avacheva, E.V. Balashov, S.P. Vikhrov, N.V. Bodyagin, S.M. Mursalov, P.E. Starov. RESEARCH OF SURFACE STRUCTURE OF THE NONCRYSTALLINE MATERIALS WITH APPLICATION OF THE SELF-ORGANIZING THEORY AND ATOMIC-FORCE MIKROSCOPY The analysis of modern research methods of a materials surface is carried out. The algorithm of account of the average mutual information between points of a material surface is described. By developed technique the surfaces of crystal, polycrystalline and noncrystalline silicon are investigated. The conclusions are made that the given technique allows to distinguish materials surfaces of various structural organization, to reveal far-working correlation in these structures118		
O.V. Rozhkov, M.A. Burobin. THE INFLUENCE OF THE SHAPE OF ELECTRODE BOUNDARY REGIONS AND WORKING HOLES ON THE POTENTIAL DISTRIBUTION IN A ION TRAP The calculation results of the multipole constituents' weighting coefficients of the potential distribution in the useful capacity of the ion trap are given. Different configurations of the electrode system boundary region are taken into consideration, as well as the influence of the electrode working holes on the potential distribution in the analyzer useful capacity		
O.A. Gorlin. THE RYAZAN STATE RADIO ENGINEERING UNIVERSITY With the use of the program of numerical modelling calculations of electronic efficiency in a nonlinear mode are carried out without taking into account a spatial charge on a 0-mode of fluctuations of the first zone of generation. It is established, that at the optimum sizes and operating modes reaches 57.45 %		
BRIEF REPORTS		
A.E. Chizhikov, S.S. Burukin. STUDY OF PROCESSES ON SURFACE OF PLASMA DISPLAY PANEL CATHODES DURING ACTIVATION IN DISCHARGE The analytical and experimental investigations of processes during activation the cold cathode of hexaborid of lanthanum in DC PDP developed. Possibility of LaB ₆ -particle melting and formation of entire thin layer on the cathode surface are confirmed		
E.V. Mamontov, V.S. Gurov, I.V. Philippov, A.A. Dyagilev. TIME-OF-FLIGHT MASS SPECTROMETER WITH LINEAR RF ELECTRIC FIELD A new RF time-of-flight mass spectrometer is described. This instrument combines two types of mass analyzers: quadrupole and time-of-flight mass spectrometers. This allows us to carry out time and space focusing of sorted ions within the linear electric RF field created by a set of plane discrete electrodes. Time-of-flight mass-spectrometer with linear RF electric field and its structure scheme are described		
R.A. Kalachik. AUTOMATIC SEGMENTATION ALGORITHM WITH SEGMENT AGGREGATION FOR IMAGE SEARCHING SYSTEMS The article deals with representation of automatic image segmentation results as a new structure named tree of segment aggregation. Modification of Kruskal's algorithm which provides		
generation of the tree is developed. Results of experiments with the algorithm are brought		

$V.V.\ Kotov,\ N.A.\ Kotova,\ V.A.\ Sokolov.$ FAIL-TOLERANCE OF SYSTEMS WITH ACTIVE RESERVICE (WITH BLOCK SWITCHING)	ING
Based on reserving scheme a Petri-Markov Net modeling a process of faults and recoveries in a system with block switching is built. A formula of fault time of system is brought	.141
A.N. Dobytchin., V.G. Matusov, V.I. Terekhin. KEY FACTOR FOR MANAGEMENT OF DEVELOPI AGENCY'S BUSINESS COST	ING
The article grounds the management features for a developing enterprise dedicated to special purpose equipment design. It also shows that proactive R&D work is required to provide strategical competitiveness of such enterprises. The authors state the fundamentals of the	
designed method for substantiation of proactive work on basis of option theory	.143
THE ITEMS OF INFORMATION ON THE AUTHORS	.147